Data Sheet

We make sure

FUJITSU COMPUTERS SIEMENS

SCALEOVIEW T17-2
17 Inch LCD TFT Display

Issue May 2005

Pages 2

Sleek, space-saving and full of visual innovation, the SCALEOVIEW T17-2 is the best choice TFT for families. It offers great performance for the home office and multimedia such as photo editing, gaming and viewing the latest DVDs. With a generous display area, great picture quality and fast response times. It is the ideal TFT for those seeking upgrade their bulky CRT.

Highlights

- Displays for differentiated demands
  - Office applications
  - Fast Internet and multimedia
  - Games are best supported
- Very easy and comfortable to use
  - Plug & Play
  - Auto-adjust
  - Easy-to-use menu

Ergonomics

- Optimum flicker-free and distortion-free ergonomics
- Excellent colour purity
- Outstanding brightness uniformity
- Wide viewing angle (160°/ 120°)
- High contrast (350:1)
- Space saving design

Technical highlights

- 17” (43cm) LCD TFT Display
- Excellent contrast 350:1
- Wide viewing angel 160°/ 120°
- High brightness 350 cd/m^2
- Amazing response time 8ms (gtg)

Reliability

- Low power consumption
- Multi-level power management
- Guaranteed quality and stability

8ms Response Time

Visible screen diagonal	17 inch (43 cm)
Graphics display (dependent on graphics processor)	
Pixels	1280 x 1024
Pixels*	800 x 600
Pixels*	640 x 480
* expanded	
Highest resolution	1280 x 1024
Text display (dependent on graphics processor)	
Pixels (max. 75Hz)	720 x 400
Picture size	338 x 270 mm
Colours	16.2 million
Pixel Pitch	0.264 mm
Frequencies	
Horizontal	30 - 82 kHz
Vertical	55 - 76 Hz
Brightness (typical)	350 cd/m^2
Contrast (typical)	350:1
Viewing angle (typical)	
Horizontal	160°
Vertical	120°
Response time (typical)	8ms
Plug and Play	VESA DDC2B

Setting options
Brightness (Back light)
Contrast
Picture position (horizontal and vertical)
Color temperature and individual color setting
Auto-adjust (direct access key)
Auto balance
Activate factory settings
Menu language

Base	
Tilt angle	-0℘ +20 °

Electrical values	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw	
Max.	51 W
Stand by	2 W
Protection class	1
Temperatures/dimensions/weight	
Ambient temperature (to IEC721)	
Working	5℃ to 35℃
Storage	-20℃ to 60℃
Dimensions (H x W x D) (With Stand)	391 x 386 x 208 mm
Weight (Monitor only)	3.2 kg
Reliability	
MTBF (demonstrated)	70,000 h
Lifetime of LCD backlight (brightness > 50 % of original brightness)	50,000 h
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and RFI suppression	CE certification according to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'99
Data cable (1.8 m) detachable on display	D-SUB (15-pin)
Power cable (1.8 m)	For wall socket Euro-Schuko-Type CEE7
External power adapter	
Plug type on power adapter	IEC-320-C13
Special features	Standardized mounting interface according VESA FPMPMI (75 mm)
Order code	S26361-K1012-V170 EAN: 4040528887666

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.

Copyright © Fujitsu Siemens Computers,09/2004

Published by

Fujitsu Siemens Computers
http://www.fujitsu-siemens.com/

Company stamp